

ISTITUTO NAZIONALE DI RICERCA METROLOGICA Repository Istituzionale

Real applications of quantum imaging

This is the author's submitted version of the contribution published as:

Original

Real applications of quantum imaging / Genovese, Marco. - In: JOURNAL OF OPTICS. - ISSN 2040-8978. - 18:7(2016), p. 073002. [10.1088/2040-8978/18/7/073002]

Availability:

This version is available at: 11696/68400 since: 2021-03-08T18:42:33Z

Publisher: IOP PUBLISHING LTD

Published DOI:10.1088/2040-8978/18/7/073002

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Institute of Physics Publishing Ltd (IOP) *Publisher copyright* IOP Publishing Ltd is not responsible for any errors or omissions in this version of the manuscript or any version derived from it.  The Version of Record is available online at DOI indicated above

Real applications of quantum imaging

Marco Genovese

INRIM, strada delle Cacce 91, 10135 Turin, Italy and CNISM, sezione di Torino Universit`a, via P.Giuria 1, 10125 Turin, Italy

E-mail: m.genovese@inrim.it

Abstract. In the last years the possibility of creating and manipulating quantum states of light has paved the way to the development of new technologies exploiting peculiar properties of quantum states, as quantum information, quantum metrology & sensing, quantum imaging ...

In particular Quantum Imaging addresses the possibility of overcoming limits of classical optics by using quantum resources as entanglement or sub-poissonian statistics. Albeit quantum imaging is a more recent field than other quantum technologies, e.g. quantum information, it is now substantially mature for application. Several different protocols have been proposed, some of them only theoretically, others with an experimental implementation and a few of them pointing to a clear application. Here we present a few of the most mature protocols ranging from ghost imaging to sub shot noise imaging and sub Rayleigh imaging.

PACS numbers: 42.50.-p,42.30.-d,42.50.St,03.65.-w

1. Introduction

In the last decade the possibility of manipulating single quantum states, and in particular photons, fostered the realization of technologies exploiting the peculiar properties of these systems (and in particular quantum correlations [1]), collectively dubbed quantum technologies [2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15].

Among quantum technologies, quantum imaging [15, 16] addresses the possibility of beating the limits of classical imaging by exploiting the peculiar properties of quantum optical states [17, 18, 19, 20, 21].

In this topical review we would like to present, without any pretension to be exhaustive, some of the most interesting examples of quantum imaging protocols that can find application in a near future. We will introduce their main features, discuss the quantum resources really needed for their implementation and, finally, describe the present state of the art of their development.

Section 2 will be devoted to ghost imaging. After introducing this technique, we will clarify what resources are really needed for this protocol and what it is achievable with classical resources. Then, a few practical applications will be presented. In section three, we will introduce sub shot noise imaging. Here we will also discuss the resources needed for this scheme. In section four, quantum illumination will be examined, comparing the original theoretical idea with experimental realizations. In section five, we will review a few schemes for sub Rayleigh imaging based on quantum light. Finally, we will hint at a few more possible developments of quantum imaging, drawing some conclusion on the future of this quantum technology.

2. The ghost imaging

Among quantum imaging techniques, ghost imaging [22] (GI) was one of the first to be proposed and attracted a large interest. This technique exploits intensity correlation fluctuations for imaging an object crossed by a beam that is revealed by a detector without any spatial resolution (bucket detector). The image of the object is retrieved when the bucket detector signal is correlated with the signal of a spatial resolving detector measuring a light beam (reference beam) whose noise (the speckles pattern $[23, 24, 25]$ is spatially correlated to this one.

This result may seem amazing sice the image is reconstructed by the spatial information gathered by the detector that did not actually interacted with the object. Nevertheless, even at an intuitive level this result can be understood from the fact that one is correlating in several different frames the fluctuations of the speckle structure of the reference beam with the effect of absorption (reflection) pattern of the imaged object on the correlated beam speckles structure.

More in detail, for realising GI, a spatially incoherent beam is addressed to an object and then collected by a bucket detector without any spatial resolution. The correlated beam, not interacting with the object, is sent to a spatially resolving detector (an array of pixels); K frames are collected. The image of the object is retrieved by measuring a function $S(x_i)$ (x_i being the position of the pixel j in the reference region):

$$
S(x_j) = f(E[N_1], E[N_2(x_j)], E[N_1N_2(x)], E[N_1^2], E[N_2^2(x_j)], \ldots),
$$

where $E[N_1^pN_2^q]$ $[2^q(x_j)], (p, q \geq 0)$ is the correlation function of N_1 , the total number of photons collected at the bucket detector, and of $N_2(x_j)$, the photon number at the jth pixel of the reference arm; $E[X]$ being the mathematical average over the set of K frames.

Substantially, in most of experimental works three main functions S have been used:

i) the Glauber intensity correlation function

$$
S(x) = G^{(2)}(x) \equiv E[N_1 N_2(x)] \tag{1}
$$

ii) the normalized intensity CF

$$
S(x) = g^{(2)}(x) \equiv G^{(2)}/(E[N_1]E[N_2(x)])
$$
\n(2)

iii) the covariance, or CF of intensity fluctuations,

$$
S(x) \equiv Cov(x) = E[(N_1 - E[N_1])(N_2(x) - E[N_2(x)])] = E[N_1 N_2(x)] - E[N_1] E[N_2(x)](3)
$$

In order to discuss the performance of different ways for realising the GI, the most significant figures of merit are the resolution and the signal-to-noise ratio (SNR) [26, 27, 28, 29]

$$
SNR_S \equiv \frac{|\langle S_{in} - S_{out} \rangle|}{\sqrt{\langle \delta^2 (S_{in} - S_{out}) \rangle}},\tag{4}
$$

where S_{in} and S_{out} are the intensity values of the reconstructed ghost image, when x_j is either inside or outside the object profile, $\delta S \equiv S - \langle S \rangle$ is the fluctuation. The SNR_S quantifies how well the image of the object is distinguishable from the background. On the other hand, the resolution is determined by the number of speckles contained in the image and quantifies the number of elementary details of the object that can be distinguished.

In view of practical application, several studies addressed a clear theoretical description [27, 30, 31, 32, 33, 34, 35] and eventual improvements of this protocol [36, 37, 38, 39, 40], as the use of high order correlation functions or differential schemes.

In particular, a systematic analysis, both theoretical and experimental, was presented [21], demonstrating, among other results, that the cases (ii) and (iii) perform very similarly in terms of SNR_S , while the case (i) performs much worse.

In the original proposal [22] and in the earliest experimental demonstrations of this technique [41] nonclassical states of light, known as twin beams, were used. These states, produced by a non-linear optical phenomenon dubbed parametric down conversion [42], PDC, (or eventually in other non-linear optical phenomena as 4-wave mixing) are correlated in photon number and are of the form

$$
|twin\rangle = \sum_{n} C_n |n\rangle |n\rangle \tag{5}
$$

where $|n\rangle$ is the n photons Fock state. They present a thermal statistics at single mode level and a speckle (each speckle corresponding to a spatial mode) structure at spatial multimode level.

Nevertheless, it was later shown, both theoretically and experimentally, that GI can be realised also with beam-split thermal light [43, 44, 45, 46, 47, 48, 49], eventually even sunlight [50], although with a smaller visibility. Indeed by considering that the field component obeys

$$
E_i^+(\mathbf{r},t) = \int d^2r' h(\mathbf{r},\mathbf{r}') \int d^3k e^{-i\mathbf{k}\mathbf{r}'} a(\mathbf{k})
$$
\n(6)

where $a(\mathbf{k})$ is the field annihilation operator for the optical mode **k** and $h(\mathbf{r}, \mathbf{r}')$ the response function of the optical path, the correlation function of intensity fluctuations can be derived for the thermal case:

$$
Cov_{TH}(\mathbf{x}) \propto \int_{bucket\ area} d\mathbf{y} |\int d\mathbf{x}' d\mathbf{y}' h_1^*(\mathbf{x}, \mathbf{x}') h_2(\mathbf{y}, \mathbf{y}') \langle a^\dagger(\mathbf{x}') a(\mathbf{y}') \rangle|^2 \tag{7}
$$

where h_1 and h_2 are the response functions on the path directed to the spatial resolving and the bucket detector respectively, while $a(\mathbf{x}) = \int d^3k e^{-i\mathbf{k}\mathbf{x}} a(\mathbf{k}).$

On the other hand for twin beams:

$$
Cov_{TB}(\mathbf{x}) \propto \int_{bucket\, area} d\mathbf{y} |\int d\mathbf{x}' d\mathbf{y}' h_1(\mathbf{x}, \mathbf{x}') h_2(\mathbf{y}, \mathbf{y}') \langle a^{\dagger}(\mathbf{x}') a(\mathbf{y}') \rangle|^2 \tag{8}
$$

4

A part some numerical factor and the presence of h_1^* instead of h_1 the two CF of intensity fluctuations are analogous. In particular [43], when $T(x)$ is the transmission function of the object to be imaged followed by a lens at a focal distance f from the object and from the detection plane, $h_2(y, y') \propto \exp(-\frac{2\pi i}{\lambda f} y \cdot y')T(y')$. When on the other path only a lens is present at a distance 2f from both the source and the detection plane, $h_1(\mathbf{x}, \mathbf{x}') = \delta(\mathbf{x} + \mathbf{x}') \exp(-\frac{i\pi}{\lambda f} |\mathbf{x}'|^2)$; by assuming that smallest scale of variation of the object spatial distribution is larger than the coherence size (speckle size), since $\langle a^{\dagger}({\bf x})a(-{\bf y})\rangle$ is non-zero in a small region around ${\bf x}' = -{\bf y}$, one finds $Cov(\mathbf{x}) \propto |T(-\mathbf{x})|^2$ for both cases.

In this sense, GI does not represent a "true" quantum imaging protocol, since it does not strictly require quantum light for being realised. Anyway, it must be mentioned that split thermal light has a non-zero discord, where non-zero discord is a weaker form of quantum correlation respect to entanglement ‡, eventually to be seen as the resource needed for GI [51]. However, the fact that GI does not really strictly needs quantum resources is even more evident in the so-called computational ghost imaging [52] (for latest developments see [53]), where discord does not play a role [54]. In this scheme a single light beam is used by modulating its pattern. The measured correlation is between the light detected by the bucket detector and the modulation pattern. This scheme also highlights the connection between GI and compressive sensing techniques [55].

In summary GI was proposed as one of the first quantum imaging examples, however its realisation does not require photon number entangled light, even if this presents some advantage, i.e. a larger visibility.

Without sticking to the discussion about "quantumness" of GI, one can consider the practical relevance of this technique. GI can be useful in the presence of phase distortions, where spatial information can be retrieved anyway [56]. This means that GI is mainly of interest in presence of a diffusive medium, a condition that appears in several significant cases, ranging from imaging in open air conditions in presence of fog to imaging of biological samples where tissues represent the diffusive medium.

 \ddagger For a bipartite (A,B) quantum state ρ the total amount of correlations is defined by the quantum mutual information

$$
I(\rho) = S(\rho_A) + S(\rho_B) - S(\rho),\tag{9}
$$

where $S(\rho) = -\text{Tr}[\rho \log_2 \rho]$ denotes von Neumann entropy. An alternative version of the quantum mutual information is

$$
J_A = S(\rho_B) - \min \sum_k p_k S(\rho_{B|k}).
$$
\n(10)

where $\rho_{B|k} = Tr_A[\Pi_k \rho \Pi_k]/Tr[\Pi_k \rho \Pi_k]$ is the conditional state of system B after obtaining outcome k on A, ${\{\Pi_k\}}$ are projective measurements on A, $p_j = Tr{\{\Pi_k \rho \Pi_k\}}$ being the probability of obtaining the outcome k. While these two definitions are equivalent in classical information, the difference between them in quantum case defines quantum discord

$$
D_A(\rho) = \mathcal{I}(\rho) - \mathcal{J}_A(\rho). \tag{11}
$$

Figure 1. Experimental set up of [75]. A 355 nm laser beam, after spatial filtering, pumps a type II BBO crystal producing twin beams. After eliminating UV beam, one correlated beam crosses a weak absorbing object and it is then addressed to a CCD camera. The other beam is directly sent to another area of CCD camera.

In the last years, progresses toward real application of the method have been realised. In particular, several works addressed the implementation of ghost imaging in turbid media [57]; in [58] was presented an application to magneto-optical Faraday microscopy, achieving an imaging of magnetic domains in garnet.

Very last experimental developments concerned GI at long distance by using optical fibers [59], GI ladar [60], GI at very low illumination level [61, 62], storing and retrieval in a quantum memory [63]...

3. The sub shot noise quantum imaging

One fundamental limit of measurement is the so called shot noise, deriving from the quantisation of carriers as photons in light beams and electrons in electric current. For classical light the limit is reached by the Poissonian statistics of coherent states, i.e. the standard deviation of shot noise is equal to the square root of the average number of photons N. For other classical states of light (e.g. thermal states) the variance is larger (super Poissonian statistics).

For what concerns imaging, this means that, due this unavoidable noise deriving from the fluctuations of the photon number, it is impossible to image a very weakly

absorbing object under a certain low illumination level, for this is lost in the noise.

A very interesting scheme for beating this limit was proposed [64], suggesting to use photon number correlations between two light beams for measuring the noise in a reference beam and subtracting it from the imaging beam. In particular, as we mentioned in the previous section, twin beams (5) have each a thermal statistics, but the fluctuations in photon number are exactly the same. Thus, the noise, in an ideal situation, can be completely eliminated by measuring it in one beam and subtracting to the other. Nevertheless, in a realistic situation the effectiveness of this method depends on the detection probability, since quantum correlations are spoiled by losses.

The effectiveness of reaching sub poissonian regime is quantified by the noise reduction factor (NRF)

$$
\sigma \equiv \langle \delta^2 (N_1 - N_2) \rangle / \langle N_1 + N_2 \rangle \approx 1 - \eta \tag{12}
$$

where N_i is the photon number in beam i=1,2 and $\delta N = N - \langle N \rangle$ (η being the total detection efficiency §).

The subpoissonian (non-classical) regime, $\sigma < 1$, has been reached in several works [66, 67, 68, 69, 70, 71, 72, 73], but in conditions that did not allow for imaging (being limited to a single spatial beam or requiring background subtraction).

A multimode subpoissonian regime without any background subtraction was finally reached [74], paving the way to the first experimental demonstration of this scheme [75, 76]. In this last work (see fig.1) two twin beams, produced by generating with a 355 nm laser beam (with 5 ns pulses) type II (opposite polarisations) PDC, were addressed (by a lens in a f-f configuration) to a high quantum efficiency (about 80% at 710 nm) CCD camera synchronized with with the pump. The multi-thermal statistics of the source (with thousands of temporal modes [77]) was quasi Poissonian with excess noise close to zero. By tayloring the mode structure [24, 25] a NRF $\sigma = 0.452(0.005)$ was achieved, allowing to beat any classical protocol and retrieving an image of a thin atomic deposition on glass with an improvement of the signal to noise ratio larger than 30% compared with the best classical imaging scheme and more than 70% better than the differential classical scheme (split thermal light beam).

Later, the advantage of this quantum protocol was enhanced reaching a NRF=0.29 [78] and the scheme was applied to microscopic regime [79].

Successively the method found further developments, for example a progress toward real time sub shot noise quantum imaging was achieved [80].

Also in this case it is interesting trying to understand which resources are really needed for realising this protocol. Evidently, entanglement is not really needed since what is required is a strict correlation in photon number fluctuations, that would be achievable with photon number Fock states if these could be efficiently generated. Anyway, in this case the need of quantum states looks to be unambiguous.

Finally, in [81] the shot noise limit was beaten for differential interference contrast microscope, a system where horizontal and vertical polarization of light are directed to

[§] Incidentally this linear dependence can be exploited for ccd calibration [65].

Figure 2. Experimental set up of the first realisation of quantum illumination [88]. A laser beam at 355 nm pumps a type II BBO crystal producing twin beams. After eliminating UV beam, the return beam is addressed to the target and combined with a thermal background, generated through an Arecchi's disk, before being addressed to a CCD camera. The other beam is directly sent to another area of CCD camera.

the sample through different optical paths, experiencing different phase shifts that are detected as a polarization rotation at the output. This scheme is limited by the shot noise. In [81] a signal to noise ration 1.35 ± 0.12 times better than the Shot Noise was reached by using a NOON state $|NOON\rangle = (|0N\rangle + |N0\rangle)/$ √ 2 with N=2 in a confocal configuration. This proof of principle is very interesting, but the possibility of building NOON states with N significantly bigger than 2 is still beyond present possibilities, strongly limiting practical use of techniques based on these states.

4. The quantum illumination

Quantum illumination (QI) was introduced in [82], expanding some previous theoretical idea [83], as a method for detecting and imaging objects in the presence of high losses and background by exploiting quantum states of light. This seminal work compared the theoretical limit for detecting an object by using single photon states in mode k, $|k\rangle$, with entangled single photons of the form $(1/\sqrt{d})\left|\sum_{k}k\right\rangle|k\rangle$, where one mode (return mode) was addressed to the object and the other (idler mode) used as a reference. An evident advantage of the quantum protocol was demonstrated even in presence of strong losses and noise: a result of the utmost interest since typically quantum protocols rapidly loose their advantage in this situation. Thus, this paper not only presented a new interesting possibility of overcoming classical limits, but also demonstrated for the first time that in certain situations quantum protocols can be robust against noise and losses, a fact not at all evident considering the extreme delicacy of previous quantum protocols.

Nevertheless, no specific detection scheme was presented and from this seminal work was not possible to directly plan an experiment. Later a progress in this sense was realised [84], considering a producible quantum optical field, a twin beam state (5), jointly with an optimum joint measurement and comparing this scheme with the optimum for every classical protocol. A 6 dB advantage of the quantum one was demonstrated.

Further progresses toward a realistic implementation were presented [85, 87, 86]. In particular, two possible detection schemes were suggested [86]. In the so called OPA receiver the return mode and the idler mode are inputs of a Optical Parametric Amplifier and the total number of photons is counted at one output port. In the Phase-Conjugate Receiver return and idler modes are inputs of a balanced difference detector.

Albeit interesting, these two detection methods rely on lossless photon counting, a detection method difficult to be realised in experiments.

A different approach was assumed in [88, 89], were the first experimental realisation of quantum illumination was realised, pointing to a simple and efficient experimental setup showing that second order correlation measurements on return and idler twin beams already suffices in guaranteeing strong advantages to the quantum protocol.

In a little more detail (fig.2), type II Parametric Down Conversion light (with correlated photon pairs of orthogonal polarisations) was generated by means of a BBO non-linear crystal pumped with the third harmonic (355 nm) of a Q-switched Nd-Yag laser, with 5 ns pulses. The correlated emissions were then addressed to a high quantum efficiency (about 80% at 710 nm) CCD camera. On one of the two paths the target object was posed. It consisted of a beam splitter combining the PDC light with a thermal background produced by addressing a laser beam to an Arecchi's rotating ground glass [90]. In a second configuration, classical, the twin beam was substituted by beam split thermal light.

The exponential advantage of QI respect to the classical method is shown in Fig.3, where the error probabilities for detecting the target are reported and compared with the experimental data of [88].

Which resource is really needed for this specific protocol was then discussed in a subsequent paper [91], where it was demonstrated as the improvement in the signalto-noise ratio achieved by the quantum sources over the classically correlated thermal ones is closely related to the respective ratio of mutual informations of return and idler beams, $MI(r : i) = S_2(\rho_r) + S_2(\rho_i) - S_2(\rho_{ri})$, with, for a Gaussian state with covariance matrix $\boldsymbol{\sigma}$, $S_2(\rho) = \frac{1}{2} \ln(\det \boldsymbol{\sigma})$.

total number of photons of the thermal background N_b
squares are the data [88] compared with the theoretical
g and QI. **Figure 3.** Results of quantum illumination protocol [88]: the error probability P_{err} of the target detection versus the total number of photons of the thermal background N_b evaluated with 10 frames. The squares are the data [88] compared with the theoretical predictions for clasiccal imaging and QI.

optimal, better exploited the photon number entanglement of twin beams (produced by pumping with a cw 780 nm laser beam a periodically poled lithium-niobate crystal) combining the return and idler modes in a OPA. The method was applied to secure quantum communication.

 Finally, recently a theoretical idea for an extension to microwave region was presented [93] and further theoretical ideas (as the use of photon subtracted photons) were discussed [92].

5. Sub Rayleigh Quantum Imaging

The wave nature of light limits the resolution achievable with a microscope, as studied by Abbe and Rayleigh. The importance of high resolution in biology, material science etc. prompted the search for methods beating Rayleigh limit (for a microscope $0.61\lambda/NA$, NA being the numerical aperture). Significant results have been reached with classical light [94], as stimulated emission depletion (STED) and ground state depletion (GSD). Nevertheless, these schemes are characterized by rather specific experimental requirements (dual laser excitation system, availability of luminescence quenching mechanisms by stimulated emission, nontrivial shaping of the quenching beam, high power); furthermore, they are not suited for applications where the fluorescence is not optically induced.

A possibility to overcome these limits or to improve these methods is offered by the

correlation properties of quantum light. As discussed in [95], the field component obeys

$$
E_i^+(\mathbf{r_i},t) = \int d^3k e^{-ikt/c} \left[\int d^2r A(\mathbf{r}) h(\mathbf{r_i},\mathbf{r}) \right] a(\mathbf{k}) \tag{13}
$$

where $a(\mathbf{k})$ is the field annihilation operator for the optical mode k, $A(\mathbf{r})$ the object aperture function and $h(\mathbf{r_i}, \mathbf{r})$ the point spread function of the imaging apparatus. When considering incoherent imaging, $P^{inc}(\mathbf{r}) \propto \int d^2r |A(\mathbf{r})h(\mathbf{r_i}, \mathbf{r})|^2$, or coherent imaging, $P^{c}(\mathbf{r}) \propto |\int d^{2}r A(\mathbf{r})h(\mathbf{r_{i}},\mathbf{r})|^{2}$, the convolution integrals produce blurred images whose amount can be gauged through the Rayleigh diffraction bound. The idea behind sub Rayleigh imaging is beating this limit by using appropriate light sources and by replacing intensity measurements with N-fold coincidence detection strategies. In particular one can envisage [95] to achieve a resolution enhancement at the standard quantum limit √ $(\propto 1/\sqrt{N}$, being N the number of photons) or at the Heisenberg bound [96] $(\propto 1/N)$ according to the procedure.

A first idea is to exploit the effective wave length of N photons systems, as biphotons produced in Parametric Down Conversion (i.e. the twin beams (5) in the low gain regime when only the two photons component is significantly different form zero). When measuring the 2nd order correlation function the interference presents a modulation corresponding to a wave length $(\lambda/2)$ reduced of a factor 2 respect to the one, λ , of the used light [97]. This allows an increased resolution in two photon detection, a result that can be extended to NOON states [98] for which one expects a correlation function

$$
G^N(\mathbf{r}, \dots, \mathbf{r}) \propto 1 + \cos N \delta(\mathbf{r}) \tag{14}
$$

with a λ/N improvement, originating a method dubbed "quantum litography" [99, 100]. Nevertheless, NOON states suffer of a strong weakness: the probability of detecting N photons arriving at the same place decreases (as the efficiency of the scheme) exponentially with N [101]. This weakness, potentially spoiling the advantage of this strategy, can be overcome with an optical centroid measurement [102]. This idea was realised [103] for 2 photons NOON states and then for 2,3 and 4 photons NOON states produced with a PDC scheme [104].

Due to the difficulty in producing light with multiphoton entanglement, as NOON states, a second strategy relies on exploiting postselection to extract the "non-classical component" from a classical state containing information about the object to be imaged. Several theoretical schemes have been proposed [95, 105]; in particular the possibility of beating Rayleigh limit by exploiting N-fold coincidence detection was highlighted [95].

A first interesting experimental realisation has been presented [106], where a laser pulse is split into two equal components, then one is shifted in phase with respect to the other, and the two components are finally allowed to interfere on a lithographic plate that functions by means of N-photon absorption. To achieve enhanced resolution by a factor of M, the process is repeated M times, incrementing the relative phase of successive laser pulses by a fixed amount. The effect of averaging M laser shots with progressively increasing phase shifts is to average out undesired spatially varying terms, leaving only a spatially uniform component of the form $\cos(2\pi M x)$ at the desired frequency (χ being the the period $2\lambda sin\theta$ of the 1-photon intensity pattern created by the interference of the two beams, with θ the angular separation between the beams). Therefore, the pattern has a resolution M-times better than that allowed by normal interferometric lithography, analogously to quantum lithography. Finally, the N-photonabsorption recording medium was simulated by Nth harmonic generation followed by a CCD camera. Here it is worth mentioning that a primary impediment to implementing these techniques is the difficulty of developing suitable N-photon absorbing media, especially for N large. Nonetheless, some idea in this sense is emerging, as dopplerons [108] or other [109].

In [110] was considered a short pulse exciting a narrow transition in a material such that the excitation lifetime is much longer than the pulse duration. If the transition is excited again by another pulse within the excitation lifetime of the first pulse, the two excitations interfere even if the two pulses do not, being mutually incoherent. As this interference occurs through the medium, the relative phase is given by the transition frequency ν and the relative delay t between the pulses. When considering a non-linear excitation of order N, the center frequency of the exciting pulse is $\nu t/N$, i.e. a "quantum interference" corresponding to a wavelength N times smaller. A proof of principle of the method was realised with rubidium atoms reaching a factor 2 under Rayleigh limit.

In [107] super–resolution was reached by illuminating an object with a laser and by post-selecting, in a SPAD array where the image is collected, only pixels that had counted exactly a certain photon number N. Indeed, in this way the 2N power of the object field transmission function is convolved with the Nth power of the receiver's point object held transmission function is convolved with the twill power of the receiver spoint spread function, an Airy function, which is \sqrt{N} times narrower than the conventional point spread function. A similar method was used in [112], where a focused laser beam scanned an object together with dynamic application of a threshold N less than the maximum count level N_{max} ; the experimental results demonstrated a sub-Rayleigh resolution enhancement by a factor of $\sqrt{\left[ln(N_{max}/N)\right]}$.

After these seminal papers, the possibility of sub Rayleigh imaging with "quantum" post-selected classical light was further explored in several more, interesting, papers. Always in the line of [95], pseudothermal light was used with second order correlation measurement [111]. Two-photon interference with subwavelength fringes has been observed for the first time with true thermal light in [113]. Further results in this line have been presented in [114].

In general for achieving super–resolution with 2nd order correlations with biphoton states one scans the two point detectors simultaneously in the same direction, being $g^{(2)}(x, y) \propto \cos[k(x+y)]$, while for thermal light one simultaneously scans the two point detectors opposite directions, being $g^{(2)}(x, y) \propto \cos[k(x - y)]$: a systematic study (both theoretical and experimental) of the best way for achieving super-resolution with second order correlation was done in Ref.[115].

Another interesting strategy is based on the use of single photon sources. A first idea in this sense was proposed [116] suggesting to achieve the super-resolved modulation of Eq. 14 by exploiting N photons emitted by N atoms. Then, it was demonstrated that by measuring the second order correlation function of two (four) single photon sources (two excited atoms) illuminating the object to be imaged the resolution improves of a factor 2 (4) [117]. The idea to exploit independent sources for achieving the super-resolved modulation of Eq. 14 was further studied, both theoretically and experimentally [118], considering a configuration of N independent emitters (thermal light sources) along a chain with equal spacing and N-1 detectors placed in a semicircle at specific angles (in this case no real quantum state preparation or detection is needed).

A very interesting method was proposed in [119] and extended and applied to NV colour centres in [120]. Here the idea is to exploit antibunching of single photon sources. In synthesis, if $\mathcal{P}(x)$ is the probability of detecting a photon from a single photon emitter, by taking the k-th power, $[\mathcal{P}(x)]^k$, the function gets narrower increasing the resolution. However, the kth power of the signal contains also products terms. The method consists in eliminating these product terms by subtracting high order correlation functions:

$$
\sum_{\alpha=1}^{2} [\mathcal{P}_{\alpha}(x)]^2 = \langle \hat{N} \rangle^2 [1 - g^{(2)}] \tag{15}
$$

$$
\sum_{\alpha=1}^{3} [\mathcal{P}_{\alpha}(x)]^3 = \langle \hat{N} \rangle^3 [1 - \frac{3}{2} g^{(2)} + \frac{1}{2} g^{(3)}] \tag{16}
$$

$$
\sum_{\alpha=1}^{4} [\mathcal{P}_{\alpha}(x)]^4 = \langle \hat{N} \rangle^4 \{ 1 - 2g^{(2)} + \frac{1}{2} [g^{(2)}]^2 + \frac{2}{3} g^{(3)} - \frac{1}{6} g^{(4)} \}
$$
(17)

$$
\sum_{\alpha=1}^{5} [\mathcal{P}_{\alpha}(x)]^{5} = \langle \hat{N} \rangle^{5} \{ 1 - \frac{5}{2} g^{(2)} + \frac{5}{4} [g^{(2)}]^{2} + \frac{5}{6} g^{(3)} + \frac{5}{12} g^{(2)} g^{(3)} - \frac{5}{24} g^{(4)} + \frac{1}{24} g^{(5)} \}
$$
\n(18)

In general, the expressions of the super-resolved images for any k have the following form:

$$
\sum_{\alpha=1}^{n} [\mathcal{P}_{\alpha}(x)]^{k} = \langle \hat{N} \rangle^{k} \sum_{i=1}^{i_{max}} y_{i} \beta_{i}, \qquad (19)
$$

with β_i representing products of the form $g^{(j_1)}(0) \cdot g^{(j_2)(0)} \cdot \ldots \cdot g^{(j_l)}(0)$.

The results of [120] are summarised in fig.4, demonstrating that the Abbe limit is beaten.

This method, due to the biocompatibility of nanodiamonds and their possible use for measuring very weak currents can find application in biology of the utmost importance [121, 122] (in fig.5 a map of single photon emission from NV centers in nanonodiamonds in neuronal cells is shown).

Finally it is worth mentioning the use of squeezed light \parallel for beating Rayleigh limit, since this allows reducing the intrinsic noise of light that limits traditional superresolution schemes [123]. In [124] 6 dB amplitude squeezed light was combined with a

 \parallel the relation between squeezing and entanglement has been discussed, for example, in [16]

Figure 4. On the top the set up of Ref. [120]: a laser scans the sample containing NV colour centers in diamond through a confocal microscope. The emission of single photon emitters is then collected and addressed to SPAD detectors. On the bottom are shown: a) a typical map of the sample, b) the direct imaging of three unresolved NV centres, c) and d) the $g^{(2)}$ and $g^{(3)}$ maps respectively, e) and f) the super resolved map for $k=2$ and $k=3$ respectively. In the inset on the right the plot of the Full Width Half Maximum characterizing the resolution, improving with the order k of the correlation function.

imaging field for tracking the motion of particles in a biological sample, beating of 42% the standard quantum limit. The same scheme was then used in [125] for realising a photonic force microscopy with a 14% resolution enhancement respect to coherent light experiments.

6. Perspectives and Conclusions

In conclusion quantum imaging is emerging as one of the most interesting quantum technologies: several protocols have been proposed, some of them with significant perspectives of real application in a next future. In this review we have described with a certain detail ghost imaging, sub shot noise imaging, quantum illumination and a few of the several proposals for beating Rayleigh diffraction limit by exploiting quantum states of light.

Being exhaustive in describing all quantum imaging proposals is rather difficult

Figure 5. Emission from NV colour centres in nanodiamonds inside hippocampal neurons.

and, probably, pointless. Therefore, we limited our choice to these few examples that are somehow paradigmatic of these quantum technologies and, in our opinion, next to application. Nevertheless, before concluding, it is worth mentioning a few other protocols of quantum imaging, as entangled imaging [126] (i.e. the generation of two correlated images by exploiting twin beams entanglement), noiseless amplification of images [127], quantum imaging with undetected photons [128] (see [129] for discussions about its interpretation) and much more [130].

Altogether we hope to have provided a panoramic view on this new interesting quantum technologies and to have shown their potentiality for a significant development in the next future.

6.1. Acknowledgments

I wish to thank all my collaborators with whom I had the pleasure to collaborate in the fascinating field of quantum imaging: A.Avella, G. Brida, A.Caprile, I. P. Degiovanni, J. Forneris, D. Gatto Monticone, K. Katamadze, E.D. Lopaeva, A.Magni, A.Meda, E. Moreva, S.Olivares, P. Olivero, I. Ruo Berchera,N.Samantaray, P. Traina. This work has been partially supported by EU through BRISQ2 project (EU FP7 under grant agreement No. 308803). We also acknowledge the support of the John Templeton Foundation (Grant ID 43467). The opinions expressed in this publication are those of the authors and do not necessarily reflect the views of the John Templeton Foundation.

7. References

- [1] Genovese M, Phys. Rep. 413(2005) and ref.s therein.
- [2] Bouwmeester D, Pan J W, Mattle K, Eibl M, Weinfurter H and Zeilinger A 1997 et al. Nature 390 575
- [3] Ursin R, Jennewein T, Aspelmeyer M, Kaltenbaek R, Lindenthal M, Walther P and Zeilinger A 2004 Nature 430 849
- [4] Boschi D, Branca S, De Martini F, Hardy L and Popescu S 1998 Phys. Rev. Lett. 80 1121
- [5] O'Brien J L 2007 Science 318 1567
- [6] Yao X C et al 2012 Nature 482 489
- [7] Yamamoto T, Koashi M, Özdemir S K and Imoto N 2003 Nature 421 343
- [8] Pan J W, Simon C, Brukner C and Zeilinger A 2001 Nature 410 1067
- [9] Pan J W, Gasparoni S, Ursin R, Weihs G and Zeilinger A 2003 Nature 417, 4174
- [10] Ruo Berchera I, Degiovanni I P, Olivares S and Genovese M 2013 Phys. Rev. Lett. 110 213601
- [11] Brida G, Castelletto S, Degiovanni I P, Genovese M, Novero C, Rastello M L 2000, Metrologia 37 629;
- [12] Brida G, Degiovanni I P, Florio A, Genovese M, Giorda P, Meda A, Paris M, Shurupov A 2010 Phys Rev Lett 104 100501
- [13] Zhang Z. et al 2013 Phys. Rev. Lett. 111 010501
- [14] Giovannetti V, Lloyd S and Maccone L 2011 Nat. Phot. 5 222
- [15] Simon S et al 2014 Int.Journ. Quant. Inf. 12 1430004
- [16] Lugiato L A et al 2002 J.Opt. B 4 S176
- [17] Kolobov M I 2007 Quantum Imaging (New York: Springer)
- [18] Treps N, Grosse N, Bowen W P, Fabre C, Bachor H A and Lam P K 2003 Science 301 5635 940
- [19] Boyer V, Marino A M, Pooser R C and Lett P D 2008 Science 321 544
- [20] Brida G, Genovese M and Ruo Berchera I 2010 Nature Photonics 4 227
- [21] Brida G et al. 2011 Phys Rev. A 83 063807
- [22] Belinskii A, Klyshko D 1994 Sov. Phys.JETP 78 259
- [23] Berzanskis A, et al 1999 Phys. Rev. A 60 1626
- [24] Brida G et al 2009 Int. Journ. Quant. Inf. 7 139
- [25] Brida G et al 2009 Journal of Modern Optics 56 201
- [26] Agafonov I N et al arXiv:0911.3718v2 [quant-ph]
- [27] Erkmen B and Shapiro J 2009 Phys. Rev. A 79, 023833
- [28] Basano L and Ottonello P 2007 Opt. Express 15, 12386
- [29] Chan K, O'Sullivan M and Boyd R 2010 Opt. Express 18 5562
- [30] Santos I, Aguirre-Gomez J and Padua S 2008 Phys. Rev. A 77, 043832
- [31] Scarcelli G, Berardi V and Shih Y 2006 Journ. Mod. Opt. 53 16
- [32] Lopaeva E and Chekhova M 2010 JETP Lett. 91 447
- [33] Erkmen E and Shapiro J 2008 Phys. Rev. A 77 043809
- [34] Degiovanni I P et al 2007 Phys. Rev. A 76 062309
- [35] Cai Y and Zhu S et al 2005 Phys. Rev. E 71 056607
- [36] Degiovanni I P et al 2007 Int.Journ. Quant. Inf. 5 33; Ferri F et al 2010 Phys. Rev. Lett. 104 253603.
- [37] Brida G et al 2011 Int. Journ. Quant. Inf. 9 341; Bai Y and Han S 2007 Phys. Rev. A 76 043828; Zhou Y et al 2010 Phys. Rev. A 81 043831; Ou L and Kuang L 2007 Journ. Phys. B 40 1833
- [38] Chen X H et al 2010 Opt. Lett. **35**, 1166
- [39] Zerom P et al 2011 Phys. Rev. A 84 061804
- [40] Puddu E et al 2007 Opt. Exp. 32 1132
- [41] Pittman T et al 1995 Phys. Rev. A 52 R3429
- [42] Avella A 2015 J. Adv. Phys. 4 252
- [43] Gatti A, Brambilla E, and Lugiato L A 2003 Phys. Rev. Lett. 90 133603; Gatti A, Brambilla E,

and Lugiato L A 2004 Phys. Rev. Lett. 93 093602; Gatti A, Brambilla E, and Lugiato L A 2004 Phys. Rev. A 70 013802; Cai Y and Zhu S 2004 Opt. Lett. 29 2716

- [44] Bennink R et al 2002 Phys. Rev. Lett. 89 113601
- [45] Ferri F et al 2005 Phys. Rev. Lett. **94** 183602
- [46] Valencia A 2005 Phys. Rev. Lett. et al 94 063601
- [47] Zhai Y H et al 2005 Phys. Rev. A 72 043805
- [48] Meyers R et al 2008 Phys. Rev. A 77 041801
- [49] Chen X et al 2010 Opt. Lett. **35** 1166
- [50] Liu X et al 2014 Opt. Lett. 39 2314; Karmakar S et al 2011 Proc. of CLEO Laser Applications to Photonic Applications, OSA Technical Digest (CD) (Optical Society of America, 2011), paper QFD3
- [51] Ragy S and Adesso G 2012 Scientific Rep. 2 1
- [52] Shapiro J 2008 Phys. Rev. A 78 061802
- [53] Zhang E et al 2015 J. Opt. 17 085602; Zafari M et al 2014 J. Opt. 16 105405; Chen W and Chen X 2015 EPL 109 14001; Hardy D and Shapiro S 2013 Phys. Rev. A 87 023820
- [54] Shapiro J H, Venkatraman D and Wong F N C 2013 Scientific. Rep. 3 1849
- [55] Tajahuerce E et al 2014 Opt. Exp. 22 16945; Farina A et al Optical Tomography and Spectroscopy of Tissue XI, Proc. of SPIE, edited by Bruce J et al , 9319K-1; Duarte M et al 2008 IEEE Sig. Proc. Mag. 88 10.1109/MSP.2007.914730
- [56] Meyers R, Deacon K S and Shih Y 2008 Phys. Rev. A 77 041801.
- [57] Gong W. and Han S.2011 *Opt. Lett.* **36** 394; Bina M *et al* 2013 *Phys. Rev. Lett.* **110** 083901; Dixon P. et al 2011 Phys. Rev. A 83 051803; Meyers R et al 2012 Applied Physics Letters 100 061126; Meyers R and Deacon K 2015 Entropy 17 1508; Meyers R et al 2012, Appl. Phys. Lett. 100 061126; Meyers R et al 2010, Appl. Phys. Lett. 98 111115; Dixon P B et al 2011 Phys. Rev. A 83 051803
- [58] Meda A et al 2015 Appl. Phys. Lett. 106 262405
- [59] Dong S et al , arXiv:1508.05248
- [60] Gong W et al , arXiv:1301.5767; Xu Y et al 2015 Chin. Phys. B 24 124202
- [61] MorrisP et al , Nat. Comm. DOI: 10.1038/ncomms6913
- [62] Aspden R et al 2013 New Journal of Physics 15 073032
- [63] Cho Y 2012 *et al Opt. Exp.* **20** 5809
- [64] Brambilla E et al . 2008 Phys. Rev. A 77 053807
- [65] Meda A et al 2014 Appl. Phys. Lett. **105** 101113; Brida G et al 2006 J.Opt.Soc. Am B 23 2185; Brida G et al 2008 Opt. Exp. 16 12550; Brida G et al 2010 Opt. Exp. 18 20572; Lindenthal M and Kofler J 2006 App. Opt. 45 6059; Perina J et al 2012 Opt. Lett. 37 2475; A. Avella et al arXiv:1601.07379 in press.
- [66] Nabors,C.D., and Shelby, R.M., 1990 Phys. Rev. A 42 556
- [67] Tapster,P.R., Seward, S.F., and Rarity, J.G. 1991 Phys. Rev. A 44 3266
- [68] Souto Ribeiro, P.H., Schwob, C., Maitre, A. and Fabre, C. 1997 Opt. Lett. 22 1893
- [69] Bondani, M., Allevi, A., Zambra, G., Paris, M. and Andreoni A 2007 Phys. Rev. A 76 013833; T.Ishkakov, M. Chekhova, G.Leuchs 2009 Phys. Rev. Lett. 102, 183602
- [70] Jedrkievicz, O. et al . 2004 Phys. Rev. Lett. 93 243601
- [71] Peřina, J et al 2012 Phys. Rev. A 85, 023816
- [72] Blanchet J. et al 2008 Phys. Rev. Lett. 101 233604
- [73] Ishkakov T *et al*, arXiv:1511.08460.
- [74] Brida,G., Caspani, L., Gatti A., Genovese,M., Meda, A., and Ruo Berchera, I. 2009 Phys. Rev. Lett. 102, 213602
- [75] Brida G, Genovese M and Ruo Berchera I 2010 Nature Phot. 4 227
- [76] Brida G, Genovese M, Meda A and Ruo Berchera I 2011 Phys. Rev. A 83, 033811
- [77] Brambilla E, Gatti A, Bache M and Lugiato L A 2004Phys. Rev. A 69, 023802
- [78] Ruo Bechera I et al ; Proc. SPIE 9225-1, Quantum Communications and Quantum Imaging XI,

(2014)

- [79] Ruo Berchera I et al in press
- [80] Lawrie B and Pooser R 2013 Opt. Exp. 217549
- [81] Ono T et al 2013 Nat. Comm. 4 2426
- [82] Lloyd S 2001 Science 321, 1463
- [83] DAriano G.,Lo Presti P. 2001 Phys. Rev. Lett. 86 4195
- [84] Tan S et al. 2008 Phys. Rev. Lett. **101**, 253601
- [85] Shapiro J H and Lloyd S 2009 New Journ. of Phys. 11, 063045
- [86] Guha S and Erkmen B I 2009 Phys. Rev. A 80, 052310
- [87] Sacchi M 2005 Phys. Rev. A 71 062340; Sacchi M 2005 Phys. Rev. A 72, 014305
- [88] Lopaeva E, Ruo Berchera I, Degiovanni I , Olivares S, Brida G, Genovese M 2013 Phys. Rev. Lett. 110 153603
- [89] Lopaeva E et al 2014 Phys. Scr. **T160** 014026.
- [90] Arecchi T F 1965 Phys. Rev. Lett. 15, 912
- [91] Ragy S et al 2014 JOSA B 31 2045
- [92] Zhang S et al Phys. Rev. A 89 062309 (2014); Kang L et al 2014 Chinese Physics Letters 31 034202; Lanzacorta M, Proc. SPIE 9461, Radar Sensor Technology XIX; and Active and Passive Signatures VI, 946113 (May 21, 2015); doi:10.1117/12.2177577; Zhang Sheng-Li et al 2015 Chinese Physics Letters 32 090301; ShengLi Zhang et al 2014 Phys. Rev. A 90 052308
- [93] Barzanjeh S et al 2015 Phys. Rev. Lett. **114** 080503
- [94] http://www.nobelprize.org/nobel-prizes/chemistry/laureates/2014/advancedchemistryprize2014.pdf
- [95] Giovannetti V et al 2009 Phys. Rev. A 79 013827
- [96] Braun D and Popescu S 2014 Quantum Metrology 2 44
- [97] Jacobson J et al 1995 Phys. Rev. Lett. 74 4835; Fonseca J et al 1999 Phys. Rev. Lett. 82 2868; Edamatsu K, Shimizu R and Itoh T 2002 Phys. Rev. Lett. 89 213601 ; Santos I et al 2003 Phys. Rev. A 67 033812;
- [98] Kim Y. et al 2011 Opt. Exp. 19 24957
- [99] Boto A et al 2000 Phys. Rev. Lett. 85 2733; DAngelo M, Chekhova M and Shih Y 2001 Phys. Rev. Lett. 87 013602; Bennink R et al 2004 Phys. Rev. Lett. 92 033601; Demartini F et al. Phys. Rev. A 77 012324; Tsang M. 2009 Phys. Rev. Lett. 102 253601
- [100] Xu D et al 2015 Appl Phys Lett 106 171104
- [101] Tsang M 2007 Phys. Rev. A 75 043813; Steuernagel O 2004 J.Opt. B 6 S606
- [102] Tsang M 2009 Phys. Rev. Lett. **102** 253601
- [103] Shih H et al 2011 Phys. Rev. Lett. **107** 083603
- [104] Rozema L et al 2014 Phys. Rev. Lett. 112 223602
- [105] Pregnell K and Pegg D 2004 J. Mod. Opt. 51 1613; Hemmer P et al 2006 Phys. Rev. Lett. 96 163603; Muthukrishnan et al 2004 J.Opt B 6 S575; Wang K et al 2004 Phys. Rev. A A 70 041801; Cao D et al 2015 Phys. Rev. A 91 053853 ; Bjork G et al Phys. Rev. Lett. 2001 86 4516; Nagasako E et al 2001 Phys. Rev. A 64 043802 ; Shimizu R et al 2003 Phys. Rev. A 67 041805
- [106] Bentley S and Boyd R 2004 Optics Express 12 5735;
- [107] Guerrieri F et al 2010 Phys. Rev. Lett. **105** 163602.
- [108] Haroche S and Hartmann F, 1972 Phys. Rev. A 6 1280; Kyrola E and Stenholm S, 1977 Opt. Commun. 22 123; Berman P R and Ziegler J 1977 Phys. Rev. A 15, 2042 (1977); Reid J and Oka T 1977 Phys. Rev. Lett. 38 67; Freund S M et al 1975 Phys. Rev. Lett. 35 1497; Bigelow N P and Prentiss M G 1990 Phys. Rev. Lett. 65 555; Tollett J J et al 1990 Phys. Rev. Lett. 65 559.
- [109] Joshi A and Osman K 2015 Eur. Phys. J. D 69 267; Chang H et al 2006 Jour. Mod. Opt. 53 2271;
- [110] Pe'er et al 2004 Optics Express 12 6600
- [111] Oh J et al 2013 Opt. Lett. **38** 682
- [112] Mouradian S et al 2011 Opt. Exp. 19 5480
- [113] Zhai Y et al 2005 Phys. Rev. A 72 043805
- [114] Zhai Y et al 2014 Appl. Phys. Lett. 105 101104; Xu-Ri Y et al 2014 CHINESE PHYSICS B 24 044203; Bobrov I et al 2014 Phys. Rev. A Phys. Rev. A 89 043814;
- [115] Liu R et al 2014 Scientific. Rep. 4 1
- [116] Thiel C *et al* 2007 *Phys. Rev. Lett.* **99** 133603
- [117] Thiel C *et al* 2009 *Phys. Rev.* A **80** 013820
- [118] Oppel S et al 2012 Phys. Rev. Lett. **109** 233603
- [119] Schwartz O and Oron D 2012 Phys. Rev. A 85 033812; Schwartz O et al 2013 Nano Lett. 13 5832
- [120] Gatto Monticone D et al 2014 Phys. Rev. Lett. 113 143602
- [121] Steinert S et al 2013 Nature Comm. 4 1607; Hall L T et al 2012 Scientific Rep. 2 401; V. Carabelli et al in press.
- [122] Forneris J 2015 Scientific Reports 5 15901 and ref.s therein.
- [123] Kolobov M and Fabre C 2000 Phys. Rev. Lett. 85 3789
- [124] Taylor M et al 2013 Nat. Phot 7 229
- [125] Taylor M *et al* 2014 *Phys. Rev.* X 4 011017
- [126] Boyer v et al 2008 Science **321** 544
- [127] Mosset A *et al* 2005 *Phys. Rev. Lett.* **94** 223603
- [128] Lemos G et al 2014 Nature **512** 409;
- [129] Ghalaii M et al arXiv:1509.02031; Shapiro J et al 2015 Scientific Rep. 5 10329; Lahiri M et al 2015 Phys. Rev. A 92 013832
- [130] Cialdi S et al 2011 Phys. Rev. A 84 043817; Jachura M and Chrapkiewicz R 2015 Opt. Lett. 40 1540; Lopez L et al 2008 Phys. Rev. Lett. 100 013604; Delaubert V et al 2008 EPL 81 44001; Pèrez-Delgado C et al 2012 Phys. Rev. Lett. 109 123601; Treps N et al 2002 Phys. Rev. Lett. 88 203601; Santos I F, Aguirre-Gomez J G and Padua S 2008 Phys. Rev. A 77 043832; Sokolov I V et al (2001) Optic. Comm 193 195; Abouraddy A et al 2004 Phys. Rev. Lett. **93** 213903; Abouraddy A et al 2002 Journ. of Am opt. Soc. B19 1174; Andreoni A et al 2006 Phys. Rev. A 74 053802