



ISTITUTO NAZIONALE DI RICERCA METROLOGICA Repository Istituzionale

Dual-laser absorption spectroscopy of C₂H₂ at 1.4 μm

This is the author's submitted version of the contribution published as:

Original

Dual-laser absorption spectroscopy of C₂H₂ at 1.4 μm / Fasci, E.; Odintsova, T. A.; Castrillo, A.; De Vizia, M. D.; Merlone, Andrea; Bertiglia, Fabio; Moretti, L.; Gianfrani, L.. - In: PHYSICAL REVIEW A. - ISSN 2469-9926. - 93:4(2016). [10.1103/PhysRevA.93.042513]

Availability:

This version is available at: 11696/54568 since: 2017-02-24T16:13:33Z

Publisher:

APS

Published

DOI:10.1103/PhysRevA.93.042513

Terms of use:

This article is made available under terms and conditions as specified in the corresponding bibliographic description in the repository

Publisher copyright

American Physical Society (APS)

Copyright © American Physical Society (APS)

(Article begins on next page)

Dual-laser absorption spectroscopy of C_2H_2 at $1.4 \mu m$

E. Fasci,¹ T. Odintsova,¹ A. Castrillo,^{1,*} M.D. De Vizia,¹ A. Merlone,² F. Bertiglia,² L. Moretti,¹ and L. Gianfrani^{1,†}

¹*Dipartimento di Matematica e Fisica, Seconda Università di Napoli, Viale Lincoln, 5 I-81100 Caserta, Italy*

²*INRIM, Istituto Nazionale di Ricerca Metrologica, Strada delle Cacce, 91 I-10135 Torino, Italy*

(Dated: April 1, 2016)

Spectroscopic parameters (line intensity factor, pressure self-broadening and shifting coefficients) of C_2H_2 at $1.4 \mu m$ were accurately measured using a dual-laser approach, based upon the technique of optical phase-locking. This generated an absolute frequency scale underneath the absorption spectra. A pair of extended-cavity diode lasers were used. One of them, the probe laser, is forced to maintain a precise frequency-offset from a reference laser, which is an optical frequency standard based on noise-immune cavity-enhanced optical heterodyne molecular spectroscopy (NICE-OHMS). Laser-gas interaction takes place inside an isothermal multi-pass cell that is stabilized at the temperature of the triple point of water. The unprecedented fidelity in the observation of the shape associated to the $P_e(14)$ line of the $2\nu_3 + \nu_5$ band allowed us to measure the spectroscopic parameters, with a global uncertainty for the linestrength of 0.22%.

PACS numbers: 33.70.Jg, 33.20.Ea, 42.62.Fi

I. INTRODUCTION

Acetylene (C_2H_2), also known as ethyne, is one of the most important non-methane hydrocarbons (NMHCs). Its spectroscopic parameters are crucial in several research fields, such as combustion science, astrophysics, Earth and planetary atmospheric chemistry. Acetylene is a minor constituent of our atmosphere [1, 2] as well as of the atmospheres of Mars [3], Jupiter [4], Titan [5], Uranus [6, 7], and Neptune [8]. It significantly contributes to the opacities of stars and plays a central role in the synthesis of various important astronomical relevant species [9]. Furthermore, it has been shown its crucial presence in some star-forming regions of the interstellar space [10].

Acetylene is one of the longest-lived NMHCs, with a mixing ratio in the range of 500-3000 ppt and an average tropospheric lifetime of the order of two months, allowing this compound to reach remote areas as well as the stratosphere. Its destruction in the Earth's atmosphere occurs by reaction with OH radicals, ozone and other oxidants. In reason of that, its influence on the Earth's climate is quite significant and accurate reconstructions of vertical profiles of this trace gas are of particular relevance. In fact, acetylene has been used as reliable tracer for anthropogenic emissions since it is mostly derived from human activities related to combustion of hydrocarbon, fossil and bio fuels, and from biomass burning. C_2H_2 is often used as indicator of combustion sources and as tracer for atmospheric transport processes and chemistry (see [11] and references therein). Furthermore, it has been shown that acetylene is also produced to a lesser extent by natural processes in oceanic water and, even though this process at the present age is not predominant, it must be accounted for to explain the presence of C_2H_2 in air bubbles stored in ancient ices [12].

As a matter of fact, quantitative information on C_2H_2 densities in a variety of environments are extremely important. Their retrieval from C_2H_2 spectra requires the precise knowledge of line positions, integrated intensities, broadening and shifting coefficients.

Acetylene has also attracted the interest of the International Committee for Weights and Measures because of its relatively strong absorption features in the International Telecommunication Union's C band (1530-1560 nm). In fact, a large variety of rovibrational C_2H_2 lines have been used as secondary frequency standards for the important field of optical telecommunications [13, 14] and the strongest lines of the near-infrared spectrum have been extensively measured by using the modern technology of optical frequency comb synthesizer [15-17]. In addition, C_2H_2 is being used as a molecular target for the spectroscopic determination of the Boltzmann constant by means of Doppler Broadening Thermometry (DBT) (see [18] and reference therein).

In the last few years, spectroscopic data regarding the near-infrared spectrum of acetylene have been noticeably enriched, especially in six different spectral regions, namely around 3, 2.2, 1.9, 1.7, 1.5, and $1.4 \mu m$ [19]. Many efforts have been done in this field, using well consolidated spectroscopic techniques, such as high-resolution Fourier transform spectrometry [20, 21], direct laser absorption spectroscopy [22], and cavity ring-down spectroscopy [23]. Interesting results have been also obtained by using spectroscopic techniques assisted by the technology of optical frequency combs [24, 25]. In most of these studies, the Voigt profile (VP) has been adopted for the aims of the spectral analysis. Nevertheless, highly-accurate experiments have already demonstrated the VP inadequacy. In fact, VP takes into account Doppler and collisional broadenings, thus neglecting second order effects such as the speed dependence of relaxation rates and the averaging effect of velocity-changing collisions. A wide variety of models have been proposed to consider these narrowing effects [26]. Very recently, a task

* Corresponding author: antonio.castrillo@unina2.it

† Correspondence can be also sent to: livio.gianfrani@unina2.it

group of the International Union of Pure and Applied Chemistry (IUPAC) has suggested the use of a new profile, named Hartmann-Tran profile (HTP) [27]. This profile, also known as partially Correlated quadratic Speed-Dependent Hard Collision Profile (pCqSDHCP) or partially Correlated quadratic Speed-Dependent NelkinGhatak Profile (pCqSDNGP), is sophisticated enough to include the two narrowing mechanisms and their physical correlations, while being very efficient to be computed [28]. The HTP model has been recently tested on H₂O [29, 30], CO₂ [31], O₂ [32], and CO [33] spectra, giving results that are consistent with more sophisticated models. Concerning acetylene, the HTP model has been successfully applied just in one case, at 1.5 μm , in coincidence with the P_e(11) line of the $\nu_1+\nu_3$ band [34].

In this work, using an absorption spectrometer based upon a pair of phase-locked extended-cavity diode lasers, we measured the P_e(14) line of the $2\nu_3+\nu_5$ band, at pressures ranging between 3 and 30 Torr (i.e., roughly 400-4000 Pa) and at the constant temperature of the triple point of water (273.16 K). The spectrometer allowed us to perform highly accurate and reproducible frequency scans around a given center frequency. This feature, in conjunction with the linearity of the detection chain, made it possible to avoid any instrumental distortion in measuring absorption line shapes, reaching an experimental accuracy limited only by the noise level. By using the HTP model, the line intensity, self-broadening and self-shifting coefficients were retrieved with a relative uncertainty of about 0.22%, 0.13% and 0.18%, respectively.

The paper is organized as follows: Section II describes the experimental setup, Section III deals with the line-shape model, while the results are presented and discussed in Section IV. Conclusions and future studies are the subject of Section V.

II. EXPERIMENTAL DETAILS

The dual-laser spectrometer, schematically reported in Figure 1, essentially consists of an extended-cavity diode laser (namely, the probe laser) with an emission wavelength in the range between 1.38 and 1.41 μm , a frequency stabilization and control unit (including a reference laser), an intensity stabilization feedback loop, and an isothermal cell.

The probe laser (PL) was phase-locked to the reference laser (RL) by using the phase-locking electronics that is shown in Figure 2. More specifically, portions of the two laser beams are focused on a fast photodetector (with a bandwidth of 12 GHz) to produce a beat-note signal which is sent to a power amplifier (model RF BAY LPA-8-17), scaled in frequency by a factor of 40 (by using a frequency divider, model RF BAY FPS-40-12), splitted into two parts and then sent to a pair of digital phase and frequency detectors (PSDs).

The former (PSD1 of Figure 2, model RF BAY PDF-

100) has an integrated loop-filter limiting its bandwidth to 10 kHz, while the latter (PSD2, model Analog Devices 9901) is much faster. The first PSD ensured a robust and reliable frequency-lock in the audio bandwidth (roughly 1 kHz for the loop controlling the extended cavity length and 10 kHz for that acting on the current driver), whereas the latter ensured an effective phase-locking between the two lasers. A radio-frequency (rf) synthesizer (model RHODE&SCHWARZ SMBV100) provides the reference rf signal for both the PSDs, as well as the tunable offset frequency between the two lasers. As a result of the action of the third loop that controls the laser current through a bias-tee, a significant narrowing of the beat-note could be observed, down to the Hz level, as shown in Figure 3. This demonstrates that the PL spectral purity could be improved up to the limit determined by the RL. In fact, from the error signal generated by PSD2, recorded by means of a digital oscilloscope over a period of 100 s and shown in the third panel (c) of Figure 3, it was possible to estimate the residual phase fluctuations, whose root-mean-square (rms) value amounts to 0.14 rad, on a loop bandwidth of about 190 kHz. This was estimated from the servo bumps that appear into the spectral shape of the closed-loop beat-note signal.

The reference laser was an optical frequency standard based on noise-immune cavity-enhanced optical heterodyne molecular spectroscopy (NICE-OHMS) [35]. More specifically, the emission frequency of an extended-cavity diode laser (ECDL) was actively stabilized against the center of a sub-Doppler H₂¹⁸O line, observed under optical saturation conditions in a high-finesse resonator [36]. We exploited the fact that NICE-OHMS provides a dispersion signal without dithering the optical cavity, likely to be employed as an error signal. The emission line width of the RL was carefully determined from measurements of the frequency-noise power spectral density. It turned out that the line width of the optical frequency standard amounts to about 7 kHz (full width at half maximum, FWHM) for an observation time of 1 ms [37].

Laser-gas interaction takes place inside an isothermal cell, actively stabilized at the temperature of the triple point of water. It consists of a spherical, Herriott-type, multiple reflection cell with a maximum path-length of 12 m in a volume of about 400 cm³. The cell is entirely in stainless steel, with electro-polished inner and outer cavity surfaces. Temperature control and measurements were done by using a pair of capsule-type standard platinum resistance thermometers (SPRTs, Hart Scientific, model 5686). The two SPRTs are placed inside the cylindrical spacer, into two holes expressly drilled in the front and in the back of the cell, with a displacement of 180°. The resulting displacement of the SPRTs sensing elements allowed for the evaluation of the maximum temperature gradient, since they are positioned in both radial and axially opposite positions. SPRTs were calibrated at INRIM (the Italian Institute for Research in Metrology) in the temperature interval between the triple point of mercury and the indium freezing point. Temperature sta-




Figure 1. (Color online) Sketch of the dual-laser spectrometer. BS: beam splitter; M: mirror; SM: spherical mirror; G: grating; L: anti-reflection coated lens; AOM: acousto-optic modulator; Ph: InGaAs photodiode; FPh: fast photodiode.




Figure 2. (Color online) Block diagram of the phase-locking electronics.

bility (as determined over one full day at the temperature of the triple point of water) was found to be at the level of 0.1 mK, while temperature homogeneity was better than 1 mK. These extraordinary performances were ensured by a sophisticated system, already described elsewhere [38], essentially made of two cylindrical chambers, one inside the other, the multipass cell being housed inside the inner one. In order to obtain acoustic and thermal insulation from the outside environment, the two chambers were kept under vacuum conditions. Two independent temperature stabilization stages were used: an auxiliary thermostat and a fine heating control, the former acting on the inner chamber (exploiting the circulation of a




Figure 3. (Color online) Panel (a): Example of beat-note between probe and reference lasers under weak (PSD2 deactivated) and tight lock (PSD2 activated) conditions. Panel (b): beat-note under tight lock with higher resolution, characterized by a signal-to-noise ratio of 60 dB, which represents an improvement of 25 dB with respect to the weak lock. Panel (c): Error signal recorded at the output of the phase detector AD9901, acquired for a total time of 100 s and with an integration time of 2 ms.

thermal fluid), the latter on the multipass cell (through a constantan heater wire, uniformly wrapped around the cell body).

As for the intensity stabilization of the probe laser, we adopted the same configuration of past experiments [39–41]. Two identical ultralow-noise 10-kHz bandwidth preamplified InGaAs photodiodes (New Focus, model 2011-FS-M) were used, the former to produce the ref-

erence signal that is required for the intensity stabilization, the latter to monitor the power on the output of the isothermal cell. A digital voltmeter, with 6 and half-digit resolution (Agilent, model 34401A), connected to a personal computer through a USB-GPIB board, was used to measure the transmitted signals.

Highly linear, accurate and reproducible frequency scans of the PL around a given center frequency were implemented by continuously tuning the rf offset-frequency. Details regarding the linearity of the frequency scale, as well as the whole detection chain, will be provided in Section IV C. A Labview code was developed to perform the step-by-step frequency scan and to acquire, for each step, the transmitted signal.

The gas pressure was measured by means of a 100-Torr capacitance manometer (model VCMT12TDA from Varian), with an accuracy of 0.25% of the reading. A turbomolecular pump was used to periodically evacuate the isothermal cell and create high-purity conditions. The acetylene sample was in a commercial bottle with a quoted concentration of 99.6%. Unfortunately, the manufacturer did not provide the uncertainty for the gas purity. In the data analysis, it was conservatively set to 1%. Regarding the isotopic content, we assumed that the C_2H_2 sample was at the natural abundance, namely with 97.7599% of $^{12}C_2H_2$.

III. LINE SHAPE MODEL

In the last three decades, the line shape theory has been widely developed and several alternatives to the VP, with increasing complexity, have been proposed [26]. A detailed review is out of the aims of this paper. Here, we just report the main equations that should be considered to generate the HTP profile. Before moving to the equations, it is important to point out that this profile, while accounting for the Dicke narrowing effect, the speed dependence of line broadening and shifting, and the partial correlation between velocity- and phase-changing collisions, offers an important advantage with respect to other sophisticated models. It can be easily and rapidly computed for two main reasons: (i) it is expressed in terms of only two complex probability functions and (ii) the speed-dependence of the relaxation rates is introduced in the framework of the so-called quadratic approximation [42, 43].

Introducing eight parameters, namely the line center frequency, ν_0 , the Doppler width, Γ_D , the mean collisional relaxation rate, Γ_0 , the mean collisional shift of the line center, Δ_0 , the parameters γ_2 and δ_2 accounting for the speed-dependence of collisional broadening and shifting, the frequency of velocity-changing collisions, ν_{VC} , and the η parameter representing the partial correlation between velocity and rotational state changes due to collisions, the HTP can be expressed as it follows [28]:

$$HTP(\nu) = \frac{1}{\pi} Re \left\{ \frac{A(\nu)}{1 - [\nu_{VC} - \eta(C_0 - \frac{3C_2}{2})]A(\nu) + (\frac{\eta C_2}{v_{a0}^2})B(\nu)} \right\}. \quad (1)$$

The terms $A(\nu)$ and $B(\nu)$ are combinations of the com-

plex probability function $w(z)$

$$w(z) = \frac{i}{\pi} \int_{-\infty}^{+\infty} \frac{e^{-t^2}}{z-t} dt = e^{-z^2} erfc(-iz) \quad (2)$$

where $erfc$ is the complementary error function, while

$$A(\nu) = \frac{\sqrt{\pi}c}{\nu_0 v_{a0}} [w(iZ_-) - w(iZ_+)],$$

$$B(\nu) = \frac{v_{a0}^2}{C_2} \left[-1 + \frac{\sqrt{\pi}}{2\sqrt{Y}} (1 - Z_-^2) w(iZ_-) - \frac{\sqrt{\pi}}{2\sqrt{Y}} (1 - Z_+^2) w(iZ_+) \right]. \quad (3)$$

In these expressions, the quantities X , Y , Z_+ , and Z_-

are given by:

$$Z_{\pm} = \sqrt{X+Y} \pm \sqrt{Y},$$

$$X = \frac{i(\nu_0 - \nu) + \tilde{C}_0}{\tilde{C}_2},$$

$$Y = \left(\frac{\nu_0 v_{a0}}{2c\tilde{C}_2} \right)^2, \quad (4)$$

where c is the vacuum speed of light and

$$\begin{aligned}\tilde{C}_0 &= (1 - \eta)(C_0 - \frac{3C_2}{2}) + \nu_{VC}, \\ \tilde{C}_2 &= (1 - \eta)C_2, \\ v_{a0} &= \sqrt{\frac{2k_B T}{M}}.\end{aligned}\quad (5)$$

In this latter equation, v_{a0} represents the most probable speed of the molecules of mass M at temperature T , while k_B is the Boltzmann constant. It must be noted that the coefficients C_0 and C_2 appearing into Eq. 5 can be expressed in terms of Γ_0 , Δ_0 , γ_2 , and δ_2 , as it follows:

$$\begin{aligned}C_0 &= \Gamma_0 + i\Delta_0 \\ C_2 &= \gamma_2\Gamma_0 + i(\delta_2\Delta_0),\end{aligned}\quad (6)$$

where, as suggested by Rohart *et al.* in Refs. [42, 43], the dependence of the relaxation rates on the molecular speed, v_a , is assumed to be:

$$\begin{aligned}\Gamma(v_a) &= \Gamma_0 \left\{ 1 + \gamma_2 \left[\left(\frac{v_a}{v_{a0}} \right)^2 - \frac{3}{2} \right] \right\} \\ \Delta(v_a) &= \Delta_0 \left\{ 1 + \delta_2 \left[\left(\frac{v_a}{v_{a0}} \right)^2 - \frac{3}{2} \right] \right\}.\end{aligned}\quad (7)$$

For the spectral analysis, we implemented a global-fitting procedure [44] inspired to the pioneering work of Benner *et al.* [45]. The global analysis of experimental profiles recorded at different gas pressures is a powerful tool for testing the validity of a line shape model. Moreover, compared to the usual adjustment of individual spectra, the global procedure has the advantage of strongly reducing the statistical correlation between free parameters. In particular, implementing some physical constrains, it is possible to share a number of free parameters, as it will be better explained in the subsequent Section. Furthermore, taking advantage of the fact that the gas temperature is known with an extremely high accuracy, the Doppler width $\Gamma_D = \frac{\nu_0}{c} \sqrt{2 \ln 2 \frac{k_B T}{M}}$ could be fixed at the value corresponding to the measured temperature (0.016665 cm^{-1} , for the $P_e(14)$ line), over the entire pressure range. As for the parameter η , it was fixed at 0.15, according to the recent findings of Ref. [34].

Finally, for the calculation of the complex probability function $w(z)$, we used the Matlab routine available in Ref. [46], which is an improvement of the Weideman approximation [47].

IV. RESULTS AND DISCUSSION

A. Data analysis and retrieval of spectroscopic parameters

In Table I, we report some useful information regarding the C_2H_2 vibration-rotation transition investigated in the present work. We also report the water line against which




Figure 4. (Color online) Examples of absorption spectra relative to the $P_e(14)$ transition acquired as a function of the gas pressure.

the RL was stabilized, along with its frequency distance from the acetylene line.

Figure 4 shows a series of transmission spectra for the $P_e(14)$ line of the $2\nu_3 + \nu_5$ C_2H_2 band, recorded at the constant temperature of the triple point of water as a function of the gas pressure, which was varied between 3 and 30 Torr. We draw the reader's attention on the occurrence of a weaker absorption line at the low-frequency side of the scan, which is not reported in the HITRAN database [48]. Looking into the line list of Ref. [21], it seems clear that such interfering line is due to the $^{13}CH^{12}CH$ molecule.

On the horizontal axis of Figure 4, we report the frequency offset of the probe laser with respect to the reference one. In this case, laser scans were 5160 MHz wide and resulted from 1032 steps of 5 MHz each. All the spectra were fitted to the following function:

$$P(\nu) = (P_0 + P_1\nu) \times \exp[-A^P g^P(\nu - \nu_0^P) - A^I g^I(\nu - \nu_0^I)] \quad (8)$$

where the parameters P_0 and P_1 account for a possible residual variation of the incident power, ν represents the frequency detuning from RL, A^P and $g^P(\nu - \nu_0^P)$ are the integrated absorbance and the line shape function of the probed line, respectively. Similarly, the quantities denoted by the superscript I refer to the $^{13}CH^{12}CH$ interfering line. As for the line shape functions, the HTP model was adopted. In the global fitting procedure, we retained P_0 and P_1 and the integrated absorbance A^P as free parameters of individual spectra, while ν_0^I and ν_0^P , γ_0^I and γ_0^P , δ_0^I and δ_0^P were shared across spectra in the whole pressure range, the quantities γ_0 and δ_0 being the self-broadening and shifting coefficients, respectively. The integrated absorbance of the interfering line, A^I , was constrained to be proportional to A^P , the proportionality factor being a free parameter, also shared among the various spectra. The two Doppler widths, Γ_D^I and Γ_D^P , were fixed at the expected values. The remaining parameters, β_{VC} , γ_2 and δ_2 , were set equal for the two lines and

Table I. Investigated C₂H₂ line, with its transition wave number and intensity factor at T₀=296 K. The reference H₂¹⁸O line, belonging to the ν₁+ν₃ band, is also reported, along with the frequency separation from the adjacent C₂H₂ line. Data are taken from the HITRAN database [48].

C ₂ H ₂ line	Rovibrational band	Number of spectra	Investigated pressures	Frequency (cm ⁻¹)	Linestrength (10 ⁻²³ cm/molecule)	Reference H ₂ ¹⁸ O line	Frequency separation (GHz)
P _e (14)	2ν ₃ +ν ₅	220	11	7183.390000	1.551	5 _{5,0} →5 _{5,1}	5.87




Figure 5. (Color online) Residuals resulting from the nonlinear least-squares fit of Eq. 8, for all the spectra of Figure 4.

shared among the spectra. It should be noted that β_{VC} represents the velocity-changing collision frequency per unit of pressure.

Figure 5 shows the residuals resulting from the application of the global-fitting procedure to the seven spectra of Figure 4. We must note the excellent agreement between the experimental data and the theoretical model, the rms of the residuals ranging from 650 to 900 μ V, mostly limited by the experimental noise. In our experimental conditions, for a laser power of 50 μ W impinging on the detector, we could calculate a voltage shot-noise limit of about 25 nV/ \sqrt{Hz} . This value is almost a factor 30000 lower than the noise observed in the absorption spectra. A possible source of noise could be ascribed to residual laser power fluctuations not properly compensated by the intensity stabilization loop. Extra noise could be also introduced either from unwanted electrical pick-up, or from

residual mechanical vibrations converted in spurious laser power fluctuations. Moreover, no clear structures could be evidenced. Also, there was no dependence on the gas pressure, circumstance that demonstrates the capability of the HTP model of modeling the absorption spectra in the entire pressure range. Another argument supporting this conclusion is related to the velocity-changing collision frequency. Several experiments have shown that there exists an upper limitation to this frequency, which is given by the diffusion theory, namely, $\nu_{VC}^{kin} = \frac{k_B T}{MD}$, where D is the mass diffusion coefficient. Furthermore, ν_{VC}^{kin} is expected to be proportional to the gas pressure, p . For acetylene molecules, the diffusion theory predicts that this proportionality factor, at 273.16 K, is equal to 0.03975 cm⁻¹/atm [49]. As a matter of fact, for η equal to 0.15, we found that the retrieved β_{VC} value was smaller than the calculated one, in agreement with the prediction. Instead, when considering η as a free parameter, an overestimated value of β_{VC} was obtained, this latter being 20% greater than the kinetic counterpart. In addition, if β_{VC} is fixed to its upper limit and η is treated as a free parameter, a correlation parameter of 0.2713(6) is found. This value is not physically meaningful since it would lead to a negative value for the quantity $\beta_{VC} - \eta\gamma_0$ (calculated from data of Table II).

The measured parameters are reported in Table II. For an easy comparison, data from previous studies [19, 20]¹, as well as those from the HITRAN database [48], have been also listed. The transition strength value, S , reported in HITRAN for the P_e(14) line has a relative uncertainty of 2-5%. Moreover, Jacquemart *et al.* estimated a mean accuracy for their line intensity measurements in the range between 3 and 5% for most of the investigated lines. They used a multi-spectrum fitting procedure based on the use of the Voigt profile to calculate the absorption coefficients of the lines, fixing at some theoretically calculated values the self-broadening coefficients and setting to zero the pressure shifting effect [19]. Our S determination results to be slightly shifted towards a higher value with respect to the others, even being in good agreement with the HITRAN value [48] and with that of Ref. [19]. On the contrary, the line intensity factor reported in Ref. [20] is significantly different from

¹ Data reported in [19] resulted from pure ¹²C₂H₂ samples (with 100% of ¹²C₂H₂ abundance). For a proper comparison with our data and with those provided by the HITRAN database, this intensity factor has been rescaled to the atmospheric isotopic abundance $I_a = 0.977599$ [48].




Figure 6. (Color online) Plot of the integrated absorbance in the multiple reflection cell as a function of the same quantity in the reference cell. The slope of the best-fit line is equal to the ratio between the multipass and reference cell lengths. The intercept is consistent with zero.

our determination, being the relative difference equal to $\sim 3\%$, namely a factor of thirty bigger than their quoted uncertainty.

As far as the self-broadening coefficient is concerned, the HITRAN value is $0.141 \text{ cm}^{-1}/\text{atm}$, with a relative uncertainty in the range 2-5%. It was obtained by theoretical extrapolation from lines belonging to 15 hot bands involving the $\nu_4=1$ and $\nu_5=1$ vibrational levels [50]. Following the recommendation given in [48], we adopted a temperature-dependent exponent for γ_0 of 0.75. This latter refers to air-broadened spectra and it was shown to be noticeably dependent on J , the experimental determinations varying from about 0.60 to 0.85 [50]. After rescaling the measured value to the reference temperature $T_0 = 296 \text{ K}$, we found a self-broadening coefficient that is $\sim 6\%$ larger than the one reported in HITRAN. However, a different choice for n , for instance $n=0.85$, would make our determination much closer to the HITRAN value. On the other hand, we note a good agreement with the value reported in Ref. [20], $\gamma_0 = 0.1522(2) \text{ cm}^{-1}/\text{atm}$ (this latter being measured at 295 K).

B. Path-length determination and line intensities retrieval

The determination of S requires the knowledge of the absorption path-length, L , and the conversion of the C_2H_2 pressures in molecular number densities.

The measurement of the path-length inside the multiple reflection cell was carried out following the procedure already described in detail elsewhere [51]. Very briefly, we compared L with a 1-m long reference cell, which for the sake of simplicity is not shown in Figure 1, simultaneously measuring the spectra in the multiple reflection cell and in the reference cell, in the presence of C_2H_2 gas samples at the same thermodynamic conditions. The




Figure 7. (Color online) Plot of the molecular number density vs the integrated absorbance. The best-fit line exhibits an excellent agreement with the experimental points. The slope of the line provides the quantity SL . The dispersion of the points, for each pressure, is not visible, being much smaller than the size of the points.

spectral analysis was performed by using the symmetric version of the speed-dependent Voigt profile, in order to retrieve the integrated absorbance in the multiple reflection cell, A^{MRC} , and in the reference cell, A^{REF} . These measurements were repeated for ten different values of the gas pressure, in coincidence with the $P_e(14)$ line. A linear fit of the A^{MRC} data as a function of A^{REF} (shown in Figure 6) allowed us to determine L , the reference cell having a length of $101.2(1) \text{ cm}$. We found $L=849(1) \text{ cm}$. The combined uncertainty resulted from a statistical contribution of 0.07% and a systematic component of 0.1% .

In Figure 7, we report the data that allowed us to determine the transition strength. In calculating the number densities, we took into account the gas purity and the gas temperature. Furthermore, we assumed the natural isotopic abundance for $^{12}\text{C}_2\text{H}_2$ molecules (as given in the HITRAN database). For each pressure, twenty repeated measurements were performed. The experimental points (220 in total) were fitted to a straight line by using a weighted total least-squares linear regression [52], so as to consider the uncertainties on the absorbance and on the number density. In order to test the quality of the fit, we could look at the reduced χ_r^2 that is equal to 0.65, for 218 degrees of freedom. If we calculate the probability $P(\chi_r^2 \geq 0.65)$, we find $P \sim 99.998\%$ which is much larger than any reasonable boundary (for instance 5%). The perfect agreement between the data points and the linear fit of Figure 7 was due to two main factors: the very high experimental reproducibility in recording absorption spectra, ensured by the repeatability of the frequency scan, and the good performances of the temperature stabilization system, as already discussed in Section II.

Since the HITRAN value refers to the temperature T_0 , it was necessary to rescale the retrieved $S(T)$ value to the

Table II. Spectroscopic parameters obtained at $T = 273.16$ K (first line) and rescaled at $T_0 = 296$ K (second line) for comparison with previous works. The quantity γ_0 was rescaled to T_0 using the equation $\gamma_0(T_0) = \gamma_0(T)\left(\frac{T}{T_0}\right)^n$, being $n=0.75$. Overall uncertainties, in parentheses, correspond to one standard deviation.

C_2H_2 line	$S(\times 10^{-23})$ (cm/molecule)	γ_0 ($\text{cm}^{-1}/\text{atm}$)	δ_0 ($\text{cm}^{-1}/\text{atm}$)	γ_2	δ_2	β_{VC} ($\text{cm}^{-1}/\text{atm}$)	$S(\times 10^{-23})$ (cm/molecule) ^a	$S(\times 10^{-23})$ (cm/molecule) ^b	$S(\times 10^{-23})$ (cm/molecule) ^c
$P_e(14)$	1.584(3)	0.1602(2)	-0.006746(12)	0.1217(2)	0.2140(6)	0.03058(7)			
$P_e(14)$	1.555(3)	0.1508(2)				0.02937(7)	1.551	1.538	1.508

^a Ref.[48]

^b Ref.[19]

^c Ref.[20]

reference temperature T_0 , using the following equation:

$$S(T_0) = S(T) \frac{Q(T)}{Q(T_0)} \left[1 - \exp\left(-\frac{hc\nu_0}{k_B T_0}\right) \right] \times \left[1 - \exp\left(-\frac{hc\nu_0}{k_B T}\right) \right]^{-1} \exp\left[-hc\frac{E}{k_B}\left(\frac{1}{T_0} - \frac{1}{T}\right)\right] \quad (9)$$

h being the Planck constant, E the energy of the lower level of the transition, in cm^{-1} , and Q the total internal partition function calculated by means of the well-known polynomial approximation [53].

C. Uncertainty budget

In this section, the complete budget of uncertainties is reported for the line intensity determination. We will distinguish among type A and type B uncertainties. The evaluation of the former is based on any valid statistical method for treating data, while type B uncertainties (including systematical deviations) are inferred from scientific judgement or other information concerning the possible values of the quantity.

Type A uncertainty is due to the statistical uncertainty of the linear fit of Figure 7 which, in turn, takes into account the type A uncertainty on the integrated absorbance and the type B uncertainty of the molecular gas density. This latter was related to the pressure measurement, whose uncertainty was 1% (a combination of the accuracy of our pressure gauge and the uncertainty on the sample purity of the gas sample). On the contrary, the contribution to the uncertainty due to the temperature (type A and B) was completely negligible, being at the level of 1×10^{-6} . From the weighted linear fit, we quoted an overall type A uncertainty of about 0.17%.

Type B contributions are ascribed to (i) the optical path-length, (ii) the detector's non-linearity, (iii) the linearity of the frequency scale, (iv) the laser emission width and (v) the partition function. As for the gas sample purity, we considered the fact that the C_2H_2 partial pressure amounted to 99.6% of the total pressure. The uncertainty on this value was included in the uncertainty on the pressure measurements; therefore, it was converted into a type A uncertainty by the weighted linear fit. The

Table III. Uncertainty budget (in terms of relative contributions, corresponding to one standard deviation) for the line intensity determination.

Contribution	Type A	Type B
Linear fit	0.17%	
Path length	0.07%	0.1%
Linearity of frequency scale		Negligible
Detectors non-linearity		0.03%
Laser emission line width		Negligible
Partition function		0.04%
Temperature	Negligible	0.0012%
Total uncertainty		0.22%

overall component associated to the optical path-length resulted to be 0.12% (a combination of 0.07% and 0.1% of type A and B uncertainties, respectively). Regarding the detector non-linearity, it is useful to remind that InGaAs photodiodes show a linearity within 0.04% (at one standard deviation) over the photocurrent range from 10^{-7} to 10^{-4} A [54]. In order to quantify its influence on the integrated absorbance, we adopted the following procedure: after simulating “non-linear” absorption spectra, we did the spectral analysis and determined the integrated absorbance, which was compared with the expected one. We found an average relative difference (over the simulated pressure range) of 3×10^{-4} . It is worth noting that the non-linearity was considered in our simulations in the form of a frequency-dependent second-order polynomial added to the vertical scale of each simulated spectrum so that the relative deviation between original and distorted spectra was 0.04%. Similarly, the analysis of numerically simulated spectra showed that the systematical contributions due to the laser line width and to the linearity of the frequency scale could be neglected. In fact, thanks to the phase-locking electronics, the spectral purity of the PL was at the level of a few kHz, namely at least a factor 10^{-5} smaller than the width of the absorption line in the worst case. On the other hand, measuring the difference between the frequency of the rf synthesizer and that of the beat-note, the non-linearity of the frequency scan was found to be smaller than one part over 10^8 for a 5-GHz scan.

Finally, a further source of type B uncertainty could

be ascribed to the partition function. Since $Q(T)$ comes into play during the rescaling of S to the reference temperature T_0 (see Eq. 9), its uncertainty must be properly taken into account. Following the outcomes of Ref. [53], we found that this additional contribution amounts to 0.04%.

Table III summarizes the complete uncertainty budget, which leads to an overall uncertainty of 0.22%.

V. CONCLUSIONS

The Hartmann-Tran profile was applied to the analysis of high-resolution measurements of the C_2H_2 absorption spectra, adopting a global fitting approach. High spectral fidelity was reached by using a dual-laser methodology. Our study evidenced the occurrence of Dicke narrowing effects and speed dependence of relaxation rates for self-colliding acetylene molecules.

The main outcome of this work is related to the unprecedented level of accuracy in the retrieval of the line intensity factor. In fact, as a result of a detailed uncertainty budget, we found that the global uncertainty (at $1-\sigma$) was equal to 0.22%, mostly limited by two factors: (i) the uncertainty in the optical path-length determination and (ii) the statistical uncertainty. We also measured the pressure broadening and shifting parameters for the $P_e(14)$ line with a precision of 0.13% and 0.18%, respectively. To the best of our knowledge, these measurements are the most accurate to date in pure C_2H_2 gas samples.

Our methodology can be easily extended to many other lines of different combinations bands pursuing the attractive idea of providing an extensive list of spectroscopic parameters. To this purpose, an optical frequency comb synthesizer could replace our reference laser, in order to have a more versatile system capable of studying lines at arbitrary frequencies.

-
- [1] R. Whitby and E. Altwicker, *Atmospheric Environment* (1967) **12**, 1289 (1978).
- [2] R. Zander, C. Rinsland, D. Ehhalt, J. Rudolph, and P. Demoulin, *Journal of Atmospheric Chemistry* **13**, 359 (1991).
- [3] D. Horn, J. M. McAfee, A. M. Winer, K. C. Herr, and G. C. Pimentel, *Icarus* **16**, 543 (1972).
- [4] P. V. Sada, G. L. Bjoraker, D. E. Jennings, G. H. McCabe, and P. N. Romani, *Icarus* **136**, 192 (1998).
- [5] R. J. V. Jr., B. R. Sandel, and D. F. Strobel, *Icarus* **170**, 91 (2004).
- [6] M. Burgdorf, G. Orton, J. van Cleve, V. Meadows, and J. Houck, *Icarus* **184**, 634 (2006).
- [7] J. Bishop, S. Atreya, F. Herbert, and P. Romani, *Icarus* **88**, 448 (1990).
- [8] B. Conrath, F. M. Flasar, R. Hanel, V. Kunde, W. Maguire, J. Pearl, J. Pirraglia, R. Samuelson, P. Gierasch, A. Weir, B. Bezar, D. Gautier, D. Cruikshank, L. Horn, R. Springer, and W. Shaffer, *Science* **246**, 1454 (1989).
- [9] K. Didriche and M. Herman, *Chemical Physics Letters* **496**, 1 (2010).
- [10] N. J. Evans, II, J. H. Lacy, and J. S. Carr, *The Astrophysical Journal* **383**, 674 (1991).
- [11] V. DufLOT, C. Wespes, L. Clarisse, D. Hurtmans, Y. Ngadi, N. Jones, C. Paton-Walsh, J. Hadji-Lazaro, C. Vigouroux, M. De Mazière, J.-M. Metzger, E. Mahieu, C. Servais, F. Hase, M. Schneider, C. Clerbaux, and P.-F. Coheur, *Atmospheric Chemistry and Physics* **15**, 10509 (2015).
- [12] M. Kanakidou, B. Bonsang, J. C. Le Roulley, G. Lambert, D. Martin, and G. Sennequier, *Nature* **333**, 51 (1988).
- [13] M. de Labacherie, K. Nakagawa, and M. Ohtsu, *Opt. Lett.* **19**, 840 (1994).
- [14] T. J. Quinn, *Metrologia* **40**, 103 (2003).
- [15] K. M. Yamada, A. Onae, F.-L. Hong, H. Inaba, and T. Shimizu, *Comptes Rendus Physique* **10**, 907 (2009).
- [16] A. Foltynowicz, T. Ban, P. Masłowski, F. Adler, and J. Ye, *Phys. Rev. Lett.* **107**, 233002 (2011).
- [17] J. Mandon, G. Guelachvili, and N. Picque, *Nature Photonics* **3**, 99 (2009).
- [18] L. Gianfrani, *Phil. Trans. R. Soc. A* **374**, 20150047 (2016).
- [19] D. Jacquemart, N. Lacome, J.-Y. Mandin, V. Dana, H. Tran, F. Gueye, O. Lyulin, V. Perevalov, and L. Rgaglia-Jarlot, *J. Quant. Spectrosc. Radiat. Transf.* **110**, 717 (2009).
- [20] O. Lyulin, J. V. Auwera, and A. Campargue, *J. Quant. Spectrosc. Radiat. Transf.* **160**, 85 (2015).
- [21] S. Robert, B. Amyay, A. Fayt, G. D. Lonardo, L. Fusina, F. Tamassia, and M. Herman, *The Journal of Physical Chemistry A* **113**, 13251 (2009), pMID: 19921941.
- [22] S. Arteaga, C. Bejger, J. Gerecke, J. Hardwick, Z. Martin, J. Mayo, E. McIlhattan, J.-M. Moreau, M. Pilkenton, M. Polston, B. Robertson, and E. Wolf, *Journal of Molecular Spectroscopy* **243**, 253 (2007), pRAHA2006, The 19th International Conference on High Resolution Molecular Spectroscopy.
- [23] S. Robert, M. Herman, A. Fayt, A. Campargue, S. Kassi, A. Liu, L. Wang, G. D. Lonardo, and L. Fusina, *Molecular Physics* **106**, 2581 (2008).
- [24] S. Twagirayezu, M. J. Cich, T. J. Sears, C. P. McRaven, and G. E. Hall, *Journal of Molecular Spectroscopy* **316**, 64 (2015).
- [25] C. McRaven, M. Cich, G. Lopez, T. J. Sears, D. Hurtmans, and A. Mantz, *Journal of Molecular Spectroscopy* **266**, 43 (2011).
- [26] J.-M. Hartmann, C. Boulet, and D. Robert, *Collisional effects on molecular spectra* (Elsevier, Amsterdam, 2008).
- [27] J. Tennyson, P. F. Bernath, A. Campargue, A. G. Császár, L. Daumont, R. R. Gamache, J. T. Hodges, D. Lisak, O. V. Naumenko, L. S. Rothman, H. Tran, N. F. Zobov, J. Buldyreva, C. D. Boone, M. D. D. Vizia, L. Gianfrani, J.-M. Hartmann, R. McPheat, D. Weidmann, J. Murray, N. H. Ngo, and O. L. Polyansky, *Pure and Applied Chemistry* **86**, 1931 (2014).
- [28] N. Ngo, D. Lisak, H. Tran, and J.-M. Hartmann,

- J. Quant. Spectrosc. Radiat. Transf. **129**, 89 (2013).
- [29] D. Lisak, A. Cygan, D. Bermejo, J. Domenech, J. Hodges, and H. Tran, J. Quant. Spectrosc. Radiat. Transf. **164**, 221 (2015).
- [30] M. D. De Vizia, A. Castrillo, E. Fasci, P. Amodio, L. Moretti, and L. Gianfrani, Phys. Rev. A **90**, 022503 (2014).
- [31] G. Larcher, X. Landsheere, M. Schwell, and H. Tran, J. Quant. Spectrosc. Radiat. Transf. **164**, 82 (2015).
- [32] J. Domyslawska, S. Wjtewicz, P. Maslowski, A. Cygan, K. Bielska, R. S. Trawinski, R. Ciurylo, and D. Lisak, J. Quant. Spectrosc. Radiat. Transf. **169**, 111 (2016).
- [33] A. Seleznev, G. Fedoseev, . Koshelev, and M. Tretyakov, J. Quant. Spectrosc. Radiat. Transf. **161**, 171 (2015).
- [34] D. Forthomme, M. Cich, S. Twagirayezu, G. Hall, and T. Sears, J. Quant. Spectrosc. Radiat. Transf. **165**, 28 (2015).
- [35] J. Ye, L.-S. Ma, and J. L. Hall, Opt. Lett. **21**, 1000 (1996).
- [36] H. Dinesan, E. Fasci, A. Castrillo, and L. Gianfrani, Opt. Lett. **39**, 2198 (2014).
- [37] H. Dinesan, E. Fasci, A. D'Addio, A. Castrillo, and L. Gianfrani, Opt. Express **23**, 1757 (2015).
- [38] A. Merlone, F. Moro, A. Castrillo, and L. Gianfrani, International Journal of Thermophysics **31**, 1360 (2010).
- [39] G. Casa, A. Castrillo, G. Galzerano, R. Wehr, A. Merlone, D. Di Serafino, P. Laporta, and L. Gianfrani, Phys. Rev. Lett. **100**, 200801 (2008).
- [40] L. Moretti, A. Castrillo, E. Fasci, M. D. De Vizia, G. Casa, G. Galzerano, A. Merlone, P. Laporta, and L. Gianfrani, Phys. Rev. Lett. **111**, 060803 (2013).
- [41] G. Casa, D. A. Parretta, A. Castrillo, R. Wehr, and L. Gianfrani, The Journal of Chemical Physics **127**, 084311 (2007).
- [42] F. Rohart, H. Mder, and H.-W. Nicolaisen, The Journal of Chemical Physics **101** (1994).
- [43] F. Rohart, A. Ellendt, F. Kaghat, and H. Mder, Journal of Molecular Spectroscopy **185**, 222 (1997).
- [44] P. Amodio, L. Moretti, A. Castrillo, and L. Gianfrani, The Journal of Chemical Physics **140**, 044310 (2014).
- [45] D. Benner, C. P. Rinsland, V. Devi, M. A. H. Smith, and D. Atkins, J. Quant. Spectrosc. Radiat. Transf. **53**, 705 (1995).
- [46] M. R. Zaghloul and A. N. Ali, ACM Trans. Math. Softw. **38**, 15:1 (2012).
- [47] J. A. C. Weideman, SIAM J. Numer. Anal. **31**, 1497 (1994).
- [48] L. Rothman, I. Gordon, Y. Babikov, A. Barbe, D. C. Benner, P. Bernath, M. Birk, L. Bizzocchi, V. Boudon, L. Brown, A. Campargue, K. Chance, E. Cohen, L. Coudert, V. Devi, B. Drouin, A. Fayt, J.-M. Flaud, R. Gamache, J. Harrison, J.-M. Hartmann, C. Hill, J. Hodges, D. Jacquemart, A. Jolly, J. Lamouroux, R. L. Roy, G. Li, D. Long, O. Lyulin, C. Mackie, S. Massie, S. Mikhailenko, H. Mller, O. Naumenko, A. Nikitin, J. Orphal, V. Perevalov, A. Perrin, E. Polovtseva, C. Richard, M. Smith, E. Starikova, K. Sung, S. Tashkun, J. Tennyson, G. Toon, V. Tyuterev, and G. Wagner, J. Quant. Spectrosc. Radiat. Transf. **130**, 4 (2013).
- [49] J. Hirschfelder, C. Curtis, and R. Bird, *Molecular theory of gases and liquids* (Wiley, New York, 1964).
- [50] D. Jacquemart, J.-Y. Mandin, V. Dana, L. Rgaliarlot, J.-J. Plateaux, D. Dcatoire, and L. Rothman, J. Quant. Spectrosc. Radiat. Transf. **76**, 237 (2003).
- [51] A. Castrillo, G. Gagliardi, G. Casa, and L. Gianfrani, Phys. Rev. A **67**, 062503 (2003).
- [52] A. Malengo and F. Pennecci, Metrologia **50**, 654 (2013).
- [53] R. Gamache, S. Kennedy, R. Hawkins, and L. Rothman, Journal of Molecular Structure **517518**, 407 (2000).
- [54] H. W. Yoon, J. J. Butler, T. C. Larason, and G. P. Eppeldauer, Metrologia **40**, S154 (2003).